

# 3M™ Single Coated FSK Facing Tape 3334

## Product Data Sheet

December 2008  
Supersedes: New

---

<b>Product Description</b>	3M Single Coated FSK Facing Tape 3334 is a bi-directionally reinforced polyethylene foil coated with a special pressure sensitive acrylic adhesive that combines superior quick stick at normal temperatures with superior low temperature performance.
----------------------------	---

---

<b>Key Features</b>	This tape has superior resistance to moisture and is recommended for use in high humidity conditions. Primarily used as a vapour seal for reinforced aluminium faced fibreglass or mineral wool thermal insulation.
---------------------	---

---

### Physical Properties

<b>Adhesive Type</b>	Acrylic
<b>Backing</b>	Aluminium Scrim Polyethylene
<b>Colour</b>	Silver
<b>Release Liner</b>	Paper
<b>Thickness</b>	0,17mm

### Performance Characteristics

<b>Peel Adhesion (PSTC 101)</b>	9.0 N/25mm
<b>Tensile Strength (PSTC 131)</b>	111.2 N/25mm
<b>Elongation (PSTC 131)</b>	7%
<b>Temperature Performance</b>	80°C

<b>Storage</b>	Store in clean dry place. Temperature of 21 °C and 50 percent relative humidity are recommended.
<b>Shelf Life</b>	3M Single Coated FSK Facing Tape 3334 has a shelf life of 12 months from date of dispatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity
<b>For Additional Information</b>	To request additional product information see address below.
<b>Important Notice</b>	<p>All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application.</p> <p>All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law</p>
<p>Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications.</p> <p>This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations</p>	



**3M Svenska AB**  
**Industri-tejp och lim**  
 Bollstanäsvägen 3  
 191 89 Sollentuna  
 Tel: 08-92 22 50  
 Fax: 08-92 22 88  
 Epost: kundservice@mmm.com  
 www.3M.se/tejp